

LED Shelf Refrigeration Light



PERFORMANCE FEATURES

Application

Open Case Refrigeration, Meat Case, Walk-in Cooler, Warehouse and Store

Luminaire (LED-SP-UBS4NW-WMRG2S)

Power: 8 Watts
Voltage: 24 VDC
CCT: 4000K
Color Rendering: 94 CRI
Environment: Wet Location

Mounting (LED-SPGLOBRACKET-TL)

3 x Mounting Brackets per light provided

Finish

White, Silver

Lifespan

Warranty: 5 Years

UL Listing

Suitable for wet locations

Power Supply (LED-SSD-60W-POWER)

Power: 60 Watts
Voltage: 24 VDC
Input Voltage: 120-277 VAC
Operating Temp. Range: -20 to +50C







Power Distribution Hub (LED-TL-LRL-TYCO6)

Product Type: 6-Way Distributor Hub
Voltage Rating: 125 VDC
Connector Type (End A): Mini HVL Plug
Housing Material: PA 6
Housing Color: White
UL Flammability Rating: UL 94V-0
Operating Temperature Range: -40 – +110 °C

SKU GUIDE

4FT Light Kit

MDMCLEDWMKIT-G2

Shelf (LED-SP-UBS4NW-WMRG2S) 	Shelf Plate Assembly (LED-TL-LRLS-HARNESS) 	Mounting Bracket Set (LED-SPGLOBRACKET-TL) 
Canopy (LED-SP-DBC4NW-WMRG2S) 	Power Supply (LED-SSD-60W-POWER) 	Distribution Hub (LED-TL-LRL-TYCO6) 

MDMCLEDWMKIT-G2 Kit includes: 3 x Shelf Light, 3 x Shelf Plate Assembly, 3 x Mounting Bracket Set
1 x Canopy, 1 x Power Supply, 1 x Power Distribution Hub

Note: LEDglo components can be ordered individually or as a kit.

